©OUTLANDER™ MAX XT™

HIGHLIGHTS

- Rotax® V-twin engine options
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- 14-in. cast-aluminum wheels
- 26-in. ITP† Terracross radial tires
- Painted plastics for premium look
- · Handlebar wind deflectors

- Heavy-duty front & rear bumpers
- Convertible Rack System (CRS) with LinQ[™] system
- Dynamic passenger comfort ergonomics
- 5.7-gal (21.4 L) water-resistant rear compartment
- 625-W magneto
- Multiposition passenger handgrips
- Raised floorboards



Iron Grey and Octane Blue / 650
Mossy Oak† Break-Up Country Camo† / 650

			mood and along a sould be dilled to so	
ENGINES	650		TIRES / WHEELS	
Туре	62 hp, R	otax 649.6 cc V-twin, liquid cooled	Front Tires	ITP Terracross 26 x 8 x 14 in.
Fuel Delivery System	Ele	ectronic Fuel Injection (EFI)	Rear Tires	(66 x 20.3 x 35.6 cm)
Transmission	CVT, P / R /	CVT, P $/$ R $/$ N $/$ H $/$ L, standard engine braking		ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm) 14-in, cast-aluminum
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential		Wheels	
Power Steering	Tri-Mod	e Dynamic Power Steering (DPS)	WIIGGIS	14-III. Cast-alullillulli
SUSPENSIONS			DIMENSIONS	CAPACITIES
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel		LxWxH	94 x 48 x 53 in. (238.8 x 121.9 x 135 cm)
Front Shocks	_	0il	Wheelbase	59 in. (149.9 cm)
Rear Suspension	Torsiona	nl Trailing arm Independent (TTI)	Ground Clearance	11 in. (27.9 cm)
Daar Chaalta		9.9 in. (25.1 cm) travel	Seat Height	34.5 in. (87.7 cm)
Rear Shocks BRAKES Front	Oil Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers Single 214 mm ventilated disc brake with hydraulic twin-piston caliper		Engine / Dry Weight*	650: 827 lb (375 kg) 850: 874 (396 kg) 1000R: 900 lb (408 kg)
Rear			Rack Capacity	Front: 100 lb (45 kg) Rear: 200 lb (90 kg)
			Storage Capacity	Rear: 5.7 gal (21.4 L)
			Towing Capacity	1,650 lb (750 kg)
			Fuel Capacity	5.4 gal (20.5 L)
EATURES				
Gauge	Speedometer, Speedome tachometer (bar hour mete	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A
			Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
			Seat	Convertible Rack System (CRS)
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers,			

WARRANTY

Factory 2-years limited warranty

handlebar wind deflectors, mudguards



